



commandCASE

IP 66

commandCASE is an elegant and economic range of diecast command and control enclosures. The highly attractive design perfectly matches our profiPLUS suspension arm system, or other modern arms systems. All models feature ergonomic handles on the front for easy positioning when suspended.

The range is available in three versions: with hinges and quick-action closure (also lockable), with hinges and screw fixing or as a fully screw fixed version. Lid supports provide strain-relief. The front is recessed to accommodate a membrane keypad, front plate or display panel. At the rear the screw channels are fitted with cover caps which also serve as edge protection. Threaded screw bosses are provided inside for mounting assemblies and components. Mounting plates, matching cable glands and other accessories are also available.

We can supply commandCASE enclosures fully customised to your requirements.

Enclosure sizes
6 sizes in 3 variants

Dimensions of L x W x H

230 x 200 x 120mm to 430 x 300 x 120mm

Additional info
Designer handles

Integrated recess in the lid for membrane keypad or front plates

End caps made from polyoxymethylene (POM), RAL 7016 anthracite grey

Integrated lid support, PP (polypropylene), RAL 7040 window grey

Optional: Quick-acting closure and hinge, narrow side (side W)

Enclosure
Die-cast aluminium alloy

EN AN-44300 DIN EN 1706

(GD AI Si 12/DIN 1725)

1° mould slope for casting ejection > internal circumference dimensions decrease by 1° towards enclosure bottom.

Fastening

On a ROLEC suspension arm system or directly attached to the wall in the version with lock and hinge - with or without designer handles

Internal mounting

M5 fastening thread on the enclosure base and in the lid

Ingress protection

IP 66 / EN 60529

Gasket

Chloroprene O-ring gasket (CR), temperature resistance: -30°C to +90°C

Optional: Silicone O-ring gasket, temperature resistance: -50°C to +140°C

Surface

Powder coating RAL 7035, light grey







Optional: Special colours

Optional: Corrosion protection




Customising

Learn more about our full customising service for installation-ready enclosures

Dimensions

Photo	Part-No.	Type	Length	Width	Height	Ingress protection	Gasket	Available Options
	193.200.000	commandCASE CC 200	230	200	120	IP 66/EN 60529	Snap closure, Hinges	Silicon-gasket, Shielding, Closure with lock, Corrosion proof coating
	193.202.000	commandCASE CC 202	330	200	120	IP 66/EN 60529	Snap closure, Hinges	Silicon-gasket, Shielding, Closure with lock, Corrosion proof coating
	193.250.000	commandCASE CC 250	280	250	120	IP 66/EN 60529	Snap closure, Hinges	Silicon-gasket, Shielding, Closure with lock, Corrosion proof coating
	193.252.000	commandCASE CC 252	380	250	120	IP 66/EN 60529	Snap closure, Hinges	Silicon-gasket, Shielding, Closure with lock, Corrosion proof coating
	193.300.000	commandCASE CC 300	330	300	120	IP 66/EN 60529	Snap closure, Hinges	Silicon-gasket, Shielding, Closure with lock, Corrosion proof coating
	193.302.000	commandCASE CC 302	430	300	120	IP 66/EN 60529	Snap closure, Hinges	Silicon-gasket, Shielding, Closure with lock, Corrosion proof coating

Variante 1 Dimensions

Photo	Part-No.	Type	Length	Width	Height	Ingress protection	Gasket	Available Options
	194.200.000	commandCASE CCS 200	230	200	120	IP 66/EN 60529	Hinges	Silicon-gasket, Shielding, Corrosion proof coating
	194.202.000	commandCASE CCS 202	330	200	120	IP 66/EN 60529	Hinges	Silicon-gasket, Shielding, Corrosion proof coating
	194.250.000	commandCASE CCS 250	280	250	120	IP 66/EN 60529	Hinges	Silicon-gasket, Shielding, Corrosion proof coating
	194.252.000	commandCASE CCS 252	380	250	120	IP 66/EN 60529	Hinges	Silicon-gasket, Shielding, Corrosion proof coating
	194.300.000	commandCASE CCS 300	330	300	120	IP 66/EN 60529	Hinges	Silicon-gasket, Shielding, Corrosion proof coating
	194.302.000	commandCASE CCS 302	430	300	120	IP 66/EN 60529	Hinges	Silicon-gasket, Shielding, Corrosion proof coating

Variante 2 Dimensions

Photo	Part-No.	Type	Length	Width	Height	Ingress protection	Gasket	Available Options
	195.200.000	commandCASE CCV 200	230	200	120	IP 66/EN 60529	Integrated lid supports	Silicon-gasket, Shielding, Corrosion proof coating
	195.202.000	commandCASE CCV 202	330	200	120	IP 66/EN 60529	Integrated lid supports	Silicon-gasket, Shielding, Corrosion proof coating
	195.250.000	commandCASE CCV 250	280	250	120	IP 66/EN 60529	Integrated lid supports	Silicon-gasket, Shielding, Corrosion proof coating
	195.252.000	commandCASE CCV 252	380	250	120	IP 66/EN 60529	Integrated lid supports	Silicon-gasket, Shielding, Corrosion proof coating
	195.300.000	commandCASE CCV 300	330	300	120	IP 66/EN 60529	Integrated lid supports	Silicon-gasket, Shielding, Corrosion proof coating
	195.302.000	commandCASE CCV 302	430	300	120	IP 66/EN 60529	Integrated lid supports	Silicon-gasket, Shielding, Corrosion proof coating